

PERMABOIS CLASSIC ¾" (19mm)						
TRADITIONAL SOLID WOOD FLOOR						
DESCRIPTION:	Traditional solid wood floor					
THICKNESS:	¾" (19mm)					
WIDTH:	3¼" (83mm)		4¼" (108mm)		5" (127mm)	
LENGTH:	12" (300mm) à 74" (1875mm)					
SPECIES:	Cherry, maple red oak,, hickory, yellow birch, american walnut					
INSTALLATION:	NAILED					
RADIANT FLOOR:	water heat system only					
PACKING:	3¼" (83mm)		4¼" (108mm)		5" (127mm)	
Quantity/box	20ft²		18 ft²		20ft²	
Box dimension	10.5" x 74" x 3.5"		9" x 76" x 3.5"		10.5" x 74" x 3.5"	
Pounds/box	45 pounds		40 pounds		45 pounds	
Pallet quantity	48 boxes (960 ft²)		48 boxes (864 ft²)		48 boxes (960 ft²)	
Pallet dimension	44" x 42" x 74"		44" x 40" x 76"		44" x 42" x 74"	
FSC CERTIFICATION:	on availability					
JANKA HARDNESS:	HICKORY: 1820 pounds					
	MAPLE: 1450 pounds					
	RED OAK: 1290 pounds					
	YELLOW BIRCH: 1260 pounds					
	AMERICAN WALNUT: 1010 pounds					
TECHNICALS RES:	SURFACE BURNING (EN ISO 9239-1:2010)					
	Flame spread 190-196 s. Time to flame out: 1717 s.					
	SURFACE BURNING (ASTM-E-84)					
	FSI (FLAME SPREAD INDEX) 95 TO 155 CLASS C (Depending on species)					